

Breakfast Nook 1/2 Inch Scale Bench

by Frank Moroz

SHORT BRACES

LONG BRACE

SIDES

Materials

Bench

Cut four bench sides from 1/16" stock, follow pattern.

2 bench backs 1/16" x 2" x 2 1/2"

2 bench seats 1/16" x 11/16" x 2"

4 seat braces 1/16 sq. x 9/16"

2 aprons 1/16" x 1/8" x 2"

Table

Cut two sides from 1/16" stock, follow pattern.

1 top 1/16" x 1 1/4" x 2 1/8"

4 braces 1/16" x 1/8" x 7/8"

1 long brace 1/16" x 3/16" x 2 1/8"


2 pegs 1/16" sq. x 3/16"

2 feet 1/16" x 1/8" x 7/8"

Assembly Instructions

Benches

- 1. Sand all pieces where necessary
- 2. Glue two sides to edge of back even with bottom.
- 3. Glue two seat braces to sides and back 11/16" from bottom of side.
- 4. Glue seat in place on top of braces and to back.



- 5. Glue apron to underside of seat against braces.
- 6. Round off front edges of seat.
- 7. Repeat for second bench.

Table

1. Drill two 1/16" holes in center of side one below the other 5/16" from top square off opening to 1/16" x 3/16".

- 2. Glue sides to underside of top 1/8" in from edge of end and centered.
- 3. Round off ends of short braces and glue to underside of top and table sides as shown in illustration.
- Slide long brace through openings in sides until an even amount protrudes from each side and mark with pencil
- 5. Drill 3/64" hole on each mark toward end of brace.
- 6. Slide back through opening so each hole is on outside of table side.
- 7. Round off two pegs and insert in hole.
- 8. Round off top edges of feet then glue to bottom of sides.
- 9. Paint the color of your choice and stencil or decorate as desired.

TABLE DIAGRAM

