



## Instructions for Market Stall Assembly



Material required: Scissors, 220 grit sandpaper, tacky glue.

1). First, use a scissors and trim off the wood feathers. Please do not sand as this could change the shape of the pieces.


2). Glue two posts (1 5/16") on either side of back wall (1 1/16" by 1 3/16"). The posts and the wall will be flush on the back. The angle will be facing the back.



3). Glue the front piece (1 1/6" wide by 5/8" tall) between the two tallest posts with the tall part of the post angle facing up.

4). Glue the front counter (1 1/16" long) in-between the posts. The shelf and posts are flush to the back.


5). Glue the sign board wood (1/32" by 1/4" by 1 5/16") to the top of the posts. Let the glue dry.




6). Glue the side counter (7/8" long) on top of corrugated side (5/8" by 7/8"). The shelf will be flush with the back. Let the glue dry.

7). Paint all the wall pieces and the corrugated roof as indicated in Step 2 of the Stars and Stripes kit instructions.


8). Glue back wall assembly about 1/8" from the back of the base. Let the glue dry.



9). Glue the side wall assembly on to the base and at a right angle to the back wall. Let the glue dry.



10). Glue the front wall assembly on to the base and at a right angle to the side wall and parallel to the back wall. Let the glue dry.



11). Glue the corrugated roof onto the stall with the corrugated side facing up. It should overhang in the front about 1/8".

